

Recirculating Chillers ProfiCool Exactus

- 19“ rack with 2 handles
- Air-cooled cooling machine
- Heat exchanger made of stainless steel in plastic tank
- Water circuit with non-corrosive materials
- Optical water level indicator
- Operating panel with electronic control and digital display
 - Alarm for high and low temperature
 - RS 485 interface
 - Remote control
 - General alarm
- Automatic by-pass valve
- Hotgas-bypass for proper temperature stability
- Pressure gauge
- Liquid level switch
- Housing powder-coated RAL 7035 (light grey)
- Tank filling port at front
- Extremely quiet
- Hose connections as user-friendly quick connections



ProfiCool Exactus PCEX 020

Model ProfiCool Exactus	PCEX 020	PCEX 055
Eff. cooling capacity at +20°C kW	1.8	5.3
Operating range °C	+15 / +30	+15 / +30
Temperature constancy K	±0.1	±0.1
Pump type	P4-GR11D	P2-GA13M
Pump capacity l/min	5-20	5-45
Pump pressure bar	0.5-4	0.7-3.5
Tank capacity litres	4.5	20
Water connection (quick conn.)	12 mm outside diameter	¾" Female
Required flow of cooling air m³/h	750	3,000
Power input kW	1.10	3.50
Operating voltage Volts/Hz/Phase	230/50-60/1	400-460/50-60/3
Weight kgs	40	70
Dimensions (WxD) mm	440x500	440x580
Height (1 rack unit = 44.5 mm) RU	7.5	17
Refrigerant	CFC-free : R404A	R404A

ProfiCool Exactus + options / accessories:

	Cat. No.
ProfiCool Exactus PCEX 020.03-KED	GUPCEX020.03-KED
ProfiCool Exactus PCEX 055.03-KEM	GUPCEX055.03-KEM
Water flow switch, brass	YPCEX6-008-055
Water flow switch, plastic	YPCEX6-009-055
Enhancement operating range +5/+30°C	MPCEX7-006-055
DI kit (operation with deionized water)	on request
Export model with special voltages / frequencies	on request

Additional accessories available on request.



ProfiCool Exactus PCEX 020
(reverse)

PCEX 020

