

Bloodbank Refrigerator LabStar Sirius

- Forced air circulation with automatic defrost and condensate evaporation
- Cooling unit top
- Operating panel with main switch
 - Electronic control with digital display
 - Visual/audible alarm device, mains-independent
 - Alarm warning for excess and insufficient temperature
 - Door alarm
 - No-volt remote alarm contact for connection to a remote alarm system
 - RS 485 port
- Self-closing and lockable door(s)
- Door hinges on right, changeable (for models with one door)
- Door seal changeable
- 7 drawers with telescopic slide-out and dividers (14 at LSSI 14004.); can be factory-fitted with 8 drawers if required (16 at LSSI 14004.)
- Interior made of stainless steel CNS
- Interior lighting
- 4 castors, 2 lockable, (LSSI 14004.. with 5 castors, 3 lockable)


Model LabStar Sirius		LSSI 5004	LSSI 7504	LSSI 14004
Version		GEWU/GEEU	GEWU/GEEU	GEWU/GEEU
Temperature range	°C:	+4	+4	+4
Content	litres (net):	525	630	1255
Ext. dimensions (WxDxH)	mm:	620x860x1997	720x860x1997	1440x860x1997
Int. dimensions (WxDxH)	mm:	500x695x1505	600x695x1505	1320x695x1505
Depth with door opened	mm:	1440	1540	1540
Weight	kgs:	105	112	178
Mains connection	volts/Hz/ph:	230/50/1	230/50/1	230/50/1
Telescopic drawers	:	7	7	14
Doors	:	1	1	2
Shipping dimensions (WxDxH)	mm:	700x880x2200	800x900x2200	1540x900x2200
Shipping weight	kgs:	115	122	195
Refrigerant	:	R134a	R134a	R134a



LabStar Sirius LSSI 7504GEWU



drawer with telescopic slide-out, made of CNS



individually partitionable telescopic drawers

LabStar Sirius + Accessories:

Outside / Inside

Cat. No.

LabStar Sirius LSSI 5004GEWU	white, glass door / CNS	GSLSSI5004GEWU
LabStar Sirius LSSI 5004GEEU	CNS, glass door / CNS	GSLSSI5004GEEU
LabStar Sirius LSSI 7504GEWU	white, glass door / CNS	GSLSSI7504GEWU
LabStar Sirius LSSI 7504GEEU	CNS, glass door / CNS	GSLSSI7504GEEU
LabStar Sirius LSSI 14004GEWU	white, glass door / CNS	GSLSSI14004GEWU
LabStar Sirius LSSI 14004GEEU	CNS, glass door / CNS	GSLSSI14004GEEU

ProfiTec Temperature Monitoring and Recording System (see sep. brochure). GPTEC4A

ProfiCaller telephone dialler (see sep. brochure). on request

Pt-100 temperature sensor, add. installed for ext. temperature recording. ZXX2-020-2L

Circular chart recorder for 7 days. ZLSSI2-031-040

6" 7-day circular charts. Pck. of 100 pieces. on request

Drawer with telescopic slide-out for LSSI 50xx, made of CNS. ZLSSI4-001

Drawer with telescopic slide-out for LSSI 75xx and LSSI 140xx, CNS. ZLSSI4-002

Interior socket, tropical design. ZLSSI1-001-01

Feet instead of castors, made of CNS (50 mm height adjustable). ZLSSI5-021-125

Duct to storage compartment 26 mm in diameter. ZLSSI1-002-26

Door hinges factory-mounted on left. ZLSSI5-001

MIN/MAX thermometer to be placed in refrigerators or freezers. ZXX2-019-001

Measuring range -50/+50°C, an add. temperature sensor is not required. ZXX2-019-011

MIN/MAX digital thermometer. Hand-held unit with digital display as well as data-hold and relative measuring function. Measuring range -200/+1370°C. An add. temperature sensor is required, eg. Cat.-No. ZXX2-022-100.

Temperature sensor for MIN/MAX thermometer ZXX2-019-011. ZXX2-022-100

Measuring range -100/+1000°C. Length 2 m. Other ranges on request.

Innovation prize

ProfiTec Intelligent Temperature Monitoring and Recording System



- For up to 4 refrigerators and/or freezers
- Readings are stored over a period up to 781 days
- Warning for excess and insufficient temperature
- Includes No-volt remote alarm contact
- The measuring protocol can be fed to PC via RS 232 port