

## Small Scale Chest Freezer ProfiMaster *Mini*

- Static cooling and manual defrost
- Low-noise refrigeration system, air-cooled
- Operating panel with electronic control and digital display (LED)
  - Visual/audible alarm device
  - Alarm warning for excess and insufficient temperature
- External housing made of stainless steel (CNS)
- Interior made of stainless steel (CNS)
- Insulated lid with hinge and magnetic seal



Small Scale Chest Freezer PMM0860EEN

<b>Model ProfiMaster</b>	<b>PMM0860EEN</b>
Temperature range	°C: -20/-50 : Other temperature ranges available on request.
Content	litres (gross): 8
Ext. dimensions (WxDxH)	mm: 370x500x580
Int. dimensions (WxDxH)	mm: 150x300x200
Weight	kgs: 35
Mains connection	: 1/N/PE ~ 230 V 50 Hz
Refrigerant CFC- and HCFC-free:	R507

ProfiMaster Mini + Accessories	Outside / Inside	Cat. No.
ProfiMaster Mini PMM0860	CNS / CNS	GTPMM0860
No-volt remote alarm contact for connection to a remote alarm system.		ZPMM2-009
ProfiTec Temperature Monitoring and Recording System (see sep. brochure).		GPTEC4A
ProfiCaller telephone dialler (see sep. brochure).		on request
Pt-100 temperature sensor, add. installed for ext. temperature recording.		ZPM2-023-2L
Forced air circulation.		on request
MIN/MAX thermometer to be placed in refrigerators or freezers.		ZXX2-019-001
Measuring range -50/+50 °C, an add. temperature sensor is not required.		
MIN/MAX digital thermometer. Hand-held unit with digital display as well as data-hold and relative measuring function. Measuring range -200/+1370 °C.		ZXX2-019-011
An add. temperature sensor is required, eg. Cat.-No. ZXX2-022-100.		
Temperature sensor for MIN/MAX thermometer ZXX2-019-011.		ZXX2-022-100
Measuring range -100/+1000 °C. Length 2 m. Other ranges on request.		

### Innovation prize

#### ProfiTec Intelligent Temperature Monitoring and Recording System



- For up to 4 refrigerators and/or freezers
- Readings are stored over a period up to 781 days
- Warning for excess and insufficient temperature
- Includes No-volt remote alarm contact
- The measuring protocol can be fed to PC via RS 232 port



MIN/MAX digital thermometer with add. temperature sensor

## Laboratory Upright Freezer ProfiLine Pegasus PLPE0186EWN



Temperature range	°C:	-40/-90
Content	litres (gross):	7
Ext. dimensions (WxDxH)	mm:	400x630x665
Int. dimensions (WxDxH)	mm:	150x143x310
Depth with door opened	mm:	960
Weight	kgs:	54
Mains connection	:	1/N/PE ~ 230 V 50-60 Hz

See separate brochure.